

WPPC-215WB-C/R/N Series

The overall use of flat aluminum alloy panel, fanless fully enclosed integrated design. Meet the requirements of different equipment in different environments. It is widely used in industrial control, military, communication, power, network, intelligent self-service terminal equipment and other automation applications.

Features

- 3mm Super Thin Front Bezel, Best for Embedded Cabinet.
- Pure flat panel IP65 dust-proof and waterproof.
- High precision aluminum alloy material.
- Self-developed fanless X86 architecture industrial motherboard
- Dual gigabit adaptive Ethernet ports for faster transmission.
- Industrial protection, applicable to various harsh environments.
- Supporting 12V-36V wide voltage power supply;
- Rich interfaces and strong extensibili.



I/O Interface



Specification

Screen Parameter

Display type	21.5" TFT LCD screen		
MAX.resolution	1920*1080(16:9)		
Viewing angle(H/V)	89/89/89/89 (L/R/U/D)		
Luminance (cd/m ²)	300 cd/m ²		
Contrast ratio	1000:1		

Touch Parameter

Touch type	10-point touch projection Capacitive touch screen	Single point Resistive touch	Non-touch
Transmittance	≥88%	≥78%	≥92%
Touch object	Hand or capacitive touch pen	Fingertip or stylus	/
Controller	USB (COM customized)	USB (COM customized)	/


Configuration

CPU	I5-6200U	I5-7200U	I5-8265U	I5-10210U
CPU frequency	2.3GHz	2.5GHz	1.6GHz	1.6GHz
Integrated graphics	Intel Iris Graphics 520	Intel HD Graphics 620	Intel UHD Graphics 620	Intel UHD Graphics 620
Memory/RAM	4GB DDR4(Optional 8GB/16GB/32GB)	4GB DDR4(Optional 8GB/16GB/32GB)	4GB DDR4(Optional 8GB/16GB/32GB/64GB)	8GB DDR4(Optional 16GB/32GB/64GB)
Storage	128GB SSD (Optional 256GB~512GB/1T~4T SSD, 1T/2T HDD)			
Wi-Fi	Dual Band 2.4GHz+5GHz		Watchdog Timer	Support
Bluetooth	BT4.0		RTC real time clock	Support
Operating system	Win7/10/11, Ubuntu/Centos/Redhat/Debian/Linux		Timer switch	Support

Power Parameter

Input voltage	DC 12V~36V	Power adapter	6200U/7200U: 24V/2.5A 8265U/10210U: 24V/4A
---------------	------------	---------------	---

Dimension



Physical Characteristic

Overall dimensions	W557 x H345 x D65mm
Installation size	W540.6 x H328.6mm
Color	Black, optional silve
Installation	Supports embedded/panel mount, Inner embedded/VESA wall mount by VESA, desktop by VESA, cantilever by VESA

Interface Parameter

PowerSW	1*PowerSW
Power interface	1*Threaded DC connector (Diameter 5.5*2.5mm)
Phoenix terminal	1*6P Phoenix terminal (1*232 with power supply + 1*DC)
USB	2*USB2.0, 2*USB3.0
Ethernet	2*LAN, 10M/100M/1000M adaptive Ethernet, 3G/4G customized
HDMI	1*HDMI output, up to 4K
SIM	1*SIM card slot (should be work with 3G/4G module)
VGA	1*VGA
Audio	1*Audio Out, Support audio output
Wi-Fi antenna	2*Wi-Fi antenna
Serial port	2*COM (The default is RS232, optional RS485/RS422)
Speaker	2*(8Ω2W)
Grounding	1*GND

Reliability Parameter

Operating temperature	-10°C~60°C (-20°C~70°C can be customized)
Storage temperature	-20°C~70°C
Relative humidity	95% non-condensing